

HC2 Serie normale - Standard duty



Suffisso UNF: Misure in pollici dei grani di bloccaggio
UNF suffix: inch sizes set screws

Tipo Type	Dimensioni - Dimensions											Coefficients di carico (N) Load ratings (N)		Peso Weight kg
	d	D	B ₁	B	C	S	d _s	G	B _s	d ₃	F	Dinamico C Dynamic C	Statico C ₀ Static C ₀	
	mm/inch													
HC204	20	47	43,7	34,2	17	17,1	M6x1	4,8	13,5	33,3	3,7	12160	6318	0,23
HC204-12	1¾	1,8504	1,720	1,3465	0,6693	0,673	¼-28UNF	0,189	0,531	1,311	0,146			0,23
HC205	25	52	44,4	34,9	17	17,5	M6x1	4,8	13,5	38,1	3,9	13300	7457	0,27
HC205-13	1⅜	2,0472	1,748	1,3740	0,6693	0,689	¼-28UNF	0,189	0,531	1,500	0,154			0,32
HC205-14	7/8													0,31
HC205-15	15/16													0,29
HC205-16	1													0,27
HC206	30											62	48,4	36,5
HC206-17	1½	2,4409	1,906	1,4370	0,7480	0,720	5/16-24UNF	0,236	0,626	1,752	0,197	0,50		
HC206-18	1⅞											0,47		
HC206-19	1¾											0,45		
HC206-20	1¼											0,42		
HC207	35											72	51,1	37,6
HC207-20	1¼	2,8346	2,012	1,4803	0,7874	0,740	5/16-24UNF	0,268	0,689	2,189	0,224	0,67		
HC207-21	1⅞											0,63		
HC207-22	1¾											0,60		
HC207-23	1⅞											0,57		
HC208	40											80	56,3	42,8
HC208-24	1½	3,1496	2,217	1,6850	0,8268	0,843	5/16-24UNF	0,268	0,720	2,374	0,244	0,84		
HC208-25	1⅞											0,80		
HC209	45											85	56,3	42,8
HC209-26	1⅞	3,3465	2,217	1,6850	0,8661	0,843	5/16-24UNF	0,268	0,720	2,5000	0,252	0,96		
HC209-27	1⅞											0,91		
HC209-28	1¾											0,87		
HC210	50											90	62,7	49,2
HC210-29	1⅞	3,5433	2,469	1,9370	0,9449	0,969	5/16-24UNF	0,268	0,720	2,752	0,256	1,14		
HC210-30	1⅞											1,08		
HC210-31	1⅞											1,02		
HC210-32	2											0,96		
HC211	55											100	71,4	55,5
HC211-32	2	3,9370	2,811	2,1850	0,9843	1,094	¾-24UNF	0,315	0,815	3,000	0,276	1,52		
HC211-33	2⅞											1,44		
HC211-34	2⅞											1,37		
HC211-35	2⅞											1,29		
HC212	60											110	77,8	61,9
HC212-36	2¼	4,3307	3,063	2,4370	1,0630	1,220	¾-24UNF	0,315	0,878	3,315	0,299	2,04		
HC212-37	2⅞											1,95		
HC212-38	2¾											1,90		
HC212-39	2⅞											1,77		
HC213	65											120	85,7	68,6
HC213-40	2½	4,7244	3,374	2,7008	1,1024	1,343	¾-24UNF	0,335	0,925	3,386	0,335	2,51		
HC213-41	2⅞											2,40		
HC214	70											125	85,7	68,6
HC214-42	2⅞	4,9213	3,374	2,7008	1,1417	1,343	¾-24UNF	0,335	0,925	3,543	0,350	2,79		
HC214-43	2⅞											2,68		
HC214-44	2¾											2,56		
HC215	75											130	92,1	75
HC215-45	2⅞	5,1181	3,626	2,9528	1,1811	1,469	¾-24UNF	0,335	0,925	4,016	0,362	3,14		
HC215-46	2⅞											3,01		
HC215-47	2⅞											2,88		
HC215-48	3											2,74		

Disponibile in acciaio inox AISI 440C - Available stainless steel AISI 440C