

SER2 Serie normale - Standard duty



Suffisso UNF: Misure in pollici dei grani di bloccaggio  
UNF suffix: inch sizes set screws

Tipo Type	Dimensioni - Dimensions												Coefficients di carico (N) Load ratings (N)		Peso Weight kg
	d	D	B	C	S	S <sub>1</sub>	T	F	J	P	G	d <sub>s</sub>	Dinamico C Dynamic C	Statico C <sub>0</sub> Static C <sub>0</sub>	
	mm/inch														
<b>SER204</b>	<b>20</b>	47	31	15,9	10,3	20,7	1,12	3,8	2,46	52,7	4,8	M6x1	9880	6200	0,21
SER204-12	¾	1,8504	1,2205	0,6260	0,406	0,815	0,044	0,150	0,097	2,075	0,189	¼-28UNF			
<b>SER205</b>	<b>25</b>	52	34,9	19	13,1	21,8	1,12	5,2	2,46	57,9	5	M6x1	10780	6980	0,27
SER205-13	1¼	2,0472	1,3740	0,7480	0,516	0,858	0,044	0,205	0,097	2,280	0,197	¼-28UNF			
SER205-14	7/8														
SER205-15	1½														
SER205-16	1														
<b>SER206</b>	<b>30</b>												62	38,1	22,2
SER206-17	1¼	2,4409	1,5000	0,8740	0,626	0,874	0,067	0,220	0,129	2,665	0,197	¼-28UNF			
SER206-18	1½														
SER206-19	1¾														
SER206-20	1¼														
<b>SER207</b>	<b>35</b>												72	42,9	23,8
SER207-20	1¼	2,8346	1,6890	0,9370	0,689	1,000	0,067	0,220	0,129	3,094	0,264	5/16-24UNF			
SER207-21	1½														
SER207-22	1¾														
SER207-23	1¾														
<b>SER208</b>	<b>40</b>												80	49,2	27,8
SER208-24	1½	3,1496	1,9370	1,0945	0,748	1,189	0,067	0,252	0,129	3,409	0,315	5/16-24UNF			
SER208-25	1¾														
<b>SER209</b>	<b>45</b>												85	49,2	27,8
SER209-26	1¾	3,3465	1,9370	1,0945	0,748	1,189	0,067	0,252	0,129	3,606	0,315	5/16-24UNF			
SER209-27	1⅞														
SER209-28	1¾														
<b>SER210</b>	<b>50</b>												90	51,6	28,6
SER210-29	1¾	3,5433	2,0315	1,1260	0,748	1,283	0,097	0,295	0,129	3,799	0,394	¾-24UNF			
SER210-30	1¾														
SER210-31	1½														
SER210-32	2														
<b>SER211</b>	<b>55</b>												100	55,6	30,2
SER211-32	2	3,9370	2,1890	1,1890	0,874	1,315	0,097	0,295	0,129	4,193	0,394	¾-24UNF			
SER211-33	2¼														
SER211-34	2½														
SER211-35	2¾														
<b>SER212</b>	<b>60</b>												110	65,1	31,8
SER212-36	2¼	4,3307	2,5630	1,2520	1,000	1,563	0,097	0,295	0,129	4,591	0,394	¾-24UNF			
SER212-37	2½														
SER212-38	2¾														
SER212-39	2¾														