

**UC2 Serie normale - Standard duty**

 Suffisso UNF: Misure in pollici dei grani di bloccaggio  
 UNF suffix: inch sizes set screws

Tipo Type	Dimensioni - Dimensions									Coefficienti di carico (N) Load ratings (N)		Peso Weight kg
	d	D	B	C	S	S <sub>1</sub>	G	ds	F	Dinamico C Dynamic C	Statico C <sub>0</sub> Static C <sub>0</sub>	
	mm/inch											
<b>UC201</b>	<b>12</b>	47	31	17	12,7	18,3	4,8	M6x1	3,7	12160	6318	0,20
UC201-8	3/4	1,8504	1,2205	0,6693	0,500	0,720	0,189	1/4-28UNF	0,146			0,19
<b>UC202</b>	<b>15</b>	47	31	17	12,7	18,3	4,8	M6x1	3,7	12160	6318	0,19
UC202-9	9/16	1,8504	1,2205	0,6693	0,500	0,720	0,189	1/4-28UNF	0,146			0,19
UC202-10	5/8											0,19
<b>UC203</b>	<b>17</b>	47	31	17	12,7	18,3	4,8	M6x1	3,7	12160	6318	0,18
UC203-11	1 1/16	1,8504	1,2205	0,6693	0,500	0,720	0,189	1/4-28UNF	0,146			0,17
<b>*UC204</b>	<b>20</b>	47	31	17	12,7	18,3	4,8	M6x1	3,7	12160	6318	0,16
UC204-12	3/4	1,8504	1,2205	0,6693	0,500	0,720	0,189	1/4-28UNF	0,146			0,16
<b>*UC205</b>	<b>25</b>	52	34,1	17	14,3	19,8	5	M6x1	3,9	13300	7457	0,20
UC205-13	1 3/16											0,24
UC205-14	7/8											0,23
UC205-15	1 1/16	2,0472	1,3425	0,6693	0,563	0,780	0,197	1/4-28UNF	0,154			0,21
UC205-16	1											0,20
<b>*UC206</b>	<b>30</b>	62	38,1	19	15,9	22,2	5	M6x1	5,0	18525	10735	0,32
UC206-17	1 1/16											0,33
UC206-18	1 1/8											0,34
UC206-19	1 3/16	2,4409	1,5000	0,7480	0,626	0,874	0,197	1/4-28UNF	0,197			0,32
UC206-20	1 1/4											0,31
<b>*UC207</b>	<b>35</b>	72	42,9	20	17,5	25,4	7	M8x1	5,7	24415	14630	0,48
UC207-20	1 1/4											0,54
UC207-21	1 3/16											0,51
UC207-22	1 3/8	2,8346	1,6890	0,7874	0,689	1,000	0,276	5/16-24UNF	0,224			0,48
UC207-23	1 7/16											0,45
<b>*UC208</b>	<b>40</b>	80	49,2	21	19	30,2	8	M8x1	6,2	27645	16910	0,64
UC208-24	1 1/2											0,68
UC208-25	1 3/16	3,1496	1,9370	0,8268	0,748	1,189	0,315	5/16-24UNF	0,244			0,65
<b>*UC209</b>	<b>45</b>	85	49,2	22	19	30,2	8	M8x1	6,4	32395	20235	0,68
UC209-26	1 3/8											0,78
UC209-27	1 11/16	3,3465	1,9370	0,8661	0,748	1,189	0,315	5/16-24UNF	0,252			0,74
UC209-28	1 3/4											0,70
<b>*UC210</b>	<b>50</b>	90	51,6	24	19	32,6	10	M10x1	6,5	33345	22135	0,80
UC210-29	1 13/16											0,92
UC210-30	1 7/8											0,87
UC210-31	1 15/16	3,5433	2,0315	0,9449	0,748	1,283	0,394	3/8-24UNF	0,256			0,82
UC210-32	2											0,78
<b>*UC211</b>	<b>55</b>	100	55,6	25	22,2	33,4	10	M10x1	7,0	41230	27930	1,11
UC211-32	2											1,26
UC211-33	2 1/16											1,20
UC211-34	2 1/8	3,9370	2,1890	0,9843	0,874	1,315	0,394	3/8-24UNF	0,276			1,15
UC211-35	2 3/16											1,09
<b>*UC212</b>	<b>60</b>	110	65,1	27	25,4	39,7	10	M10x1	7,6	49780	34390	1,54
UC212-36	2 1/4											1,67
UC212-37	2 3/16	4,3307	2,5630	1,0630	1,000	1,563	0,394	3/8-24UNF	0,299			1,59
UC212-38	2 3/8											1,52
UC212-39	2 1/2									1,45		
<b>UC213</b>	<b>65</b>	120	65,1	28	25,4	39,7	10	M10x1	8,5	54340	38095	1,85
UC213-40	2 1/2											1,94
UC213-41	2 3/16	4,7244	2,5630	1,1024	1,000	1,563	0,394	3/8-24UNF	0,335			1,85
<b>UC214</b>	<b>70</b>	125	74,6	29	30,2	44,4	12	M12x1,5	8,9	59090	41895	2,05
UC214-42	2 3/8											2,26
UC214-43	2 11/16	4,9213	2,9370	1,1417	1,189	1,748	0,472	7/16-20UNF	0,350			2,16
UC214-44	2 3/4											2,06
<b>UC215</b>	<b>75</b>	130	77,8	30	33,3	44,5	12	M12x1,5	9,2	64030	45885	2,21
UC215-45	2 13/16											2,46
UC215-46	2 7/8											2,35
UC215-47	2 15/16	5,1181	3,0630	1,1811	1,311	1,752	0,472	7/16-20UNF	0,362			2,24
UC215-48	3											2,12
<b>UC216</b>	<b>80</b>	140	82,6	32	33,3	49,3	12	M12x1,5	9,5	69065	50350	2,80
UC216-49	3 1/16											2,98
UC216-50	3 1/8	5,5118	3,2520	1,2598	1,311	1,9409	0,472	7/16-20UNF	0,374			2,85
UC216-51	3 3/16											2,72
<b>UC217</b>	<b>85</b>	150	85,7	34	34,1	51,6	12	M12x1,5	10,2	79800	58805	3,46
UC217-52	3 3/4											3,68
UC217-53	3 3/8	5,9055	3,3740	1,3386	1,343	2,031	0,472	7/16-20UNF	0,402			3,54
UC217-55	3 1/2											3,25
<b>UC218</b>	<b>90</b>	160	96	36	39,7	56,3	12	M12x1,5	11,2	91295	67925	4,36
UC218-56	3 1/2	6,2992	3,7795	1,4173	1,5630	2,217	0,472	7/16-20UNF	0,441			4,47

Disponibile in acciaio inox AISI 440C - Available stainless steel AISI 440C

\*Fornito con schermo antipolvere a stella, grano con sfera e anello interno brunito - Equipped with anti-rust shield star shape, screw with ball and burnished inner ring