



Tipo Type	Dimensioni - Dimensions									Coefficients di carico (N) Load ratings (N)		Peso Weight kg
	d	D	B	C	d <sub>1</sub>	B <sub>1</sub>	B <sub>2</sub>	d <sub>2</sub>	F	Dinamico C Dynamic C	Statico C <sub>0</sub> Static C <sub>0</sub>	
	mm/inch											
<b>UK305+H2305</b>	25	62	26	20	<b>20</b>	35	8	38	5,0	20140	10355	0,48
UC305+HE2305	0,9843	2,4409	1,0236	0,7874	¾	1,378	0,315	1,496	0,197			
<b>UK306+H2306</b>	30	72	29	23	<b>25</b>	38	8	45	5,9	25365	14250	0,59
UK306+HS2306	1,1811	2,8346	1,1417	0,9055	7/8	1,496	0,315	1,772	0,232			
UK306+HE2306					1							
<b>UK307+H2307</b>	35	80	33	25	<b>30</b>	43	9	52	6,8	31730	18335	0,76
UK307+HS2307	1,3780	3,1496	1,2992	0,9843	1 1/8	1,693	0,354	2,047	0,268			
<b>UK308+H2308</b>	40	90	34	27	<b>35</b>	46	10	58	7,4	38665	22800	1,07
UK308+HE2308	1,5748	3,5433	1,3386	1,0630	1 1/4	1,811	0,394	2,283	0,291			
UK308+HS2308					1 3/8							
<b>UK309+H2309</b>	45	100	37	29	<b>40</b>	50	11	65	7,4	46455	28025	1,31
UK309+HA2309					1 7/16							
UK309+HE2309	1,7717	3,9370	1,4567	1,1417	1 1/2	1,969	0,433	2,559	0,291			
UK309+HS2309					1 5/8							
<b>UK310+H2310</b>	50	110	41	32	<b>45</b>	55	12	70	8,1	58900	36385	1,70
UK310+HS2310					1 5/8							
UK310+HA2310	1,9685	4,3307	1,6142	1,2598	1 7/16	2,165	0,472	2,756	0,319			
UK310+HE2310					1 3/4							
<b>UK311+H2311</b>	55	120	44	34	<b>50</b>	59	12	75	8,5	68020	42750	2,06
UK311+HS2311					1 7/8							
UK311+HA2311	2,1654	4,7244	1,7323	1,3386	1 5/8	2,323	0,472	2,953	0,335			
UK311+HE2311					2							
<b>UK312+H2312</b>	60	130	47	36	<b>55</b>	62	13	80	9	77805	49590	2,58
UK312+HS2312	2,3622	5,1181	1,8504	1,4173	2 1/8	2,441	0,512	3,150	0,354			
<b>UK313+H2313</b>	65	140	49	39	<b>60</b>	65	14	85	10,1	88065	56905	3,07
UK313+HA2313					2 3/16							
UK313+HE2313	2,5591	5,5118	1,9291	1,5354	2 1/4	2,559	0,551	3,346	0,398			
UK313+HS2313					2 3/8							
<b>UK315+H2315</b>	75	160	55	43	<b>65</b>	73	15	98	11	107350	73340	4,82
UK315+HA2315					2 5/16							
UK315+HE2315	2,9528	6,2992	2,1654	1,6929	2 1/2	2,874	0,591	3,858	0,433			
<b>UK316+H2316</b>	80	170	58	45	<b>70</b>	78	17	105	11,4	116850	82365	5,63
UK316+HA2316					2 7/16							
UK316+HE2316	3,1496	6,6929	2,2835	1,7717	2 3/4	3,071	0,669	4,134	0,449			
<b>UK317+H2317</b>	85	180	60	47	<b>75</b>	82	18	110	12,0	126350	91960	6,47
UK317+HA2317					2 5/8							
UK317+HE2317	3,3465	7,0866	2,3622	1,8504	3	3,228	0,709	4,331	0,472			
<b>UK318+H2318</b>	90	190	64	49	<b>80</b>	86	18	120	12,3	135850	101650	7,52
UK318+HA2318					3 1/16							
UK318+HE2318	3,5433	7,4803	2,5197	1,9291	3 3/16	3,386	0,709	4,724	0,484			

Bussole HA; HE; HS con filettatura in pollici - Inch dimension adapter sleeves HA; HE; HS